



Technical Data Sheet

Aquasafe Glossy Antistatic Coating

Performance Features:

- Outstanding antistatic property
- Good adhesion to various films
- High transparency
- Excellent water resistance
- Excellent scratch and abrasion resistance
- Low VOC

Product Description:

Waterborne antistatic coating designed for Gravure or Flexo printing. Rapid surface static charge dissipation.

Typical Properties:

Appearance:	Off-White Liquid
Solids:	27% - 28%
PH:	7.5 - 8.0
Viscosity, CPS:	300 - 500
Density:	1.0 – 1.1
Manufacturing location:	USA

Handling & Storage/Stability:

The product is stable under normal room temperature. Ideal storage temperature is 40°F to 80°F. Prevent Freezing.

Market Uses:

- PET, PE, BOPP Films
- Paper

Application Methods:

The viscosity of the coating can be applied with Gravure, Flexo, or other Coating methods. Recommended 2-4 GSM dry coat weight to achieve 10^7 - 10^8 Ohms-per-square surface resistivity.

Custom Solution:

Matte version available upon request.

Product Safety:

- SDS available upon request

POLYTEX® ENVIRONMENTAL INKS, INC.

We create infinite solutions and provide first-class customer services

R&D: 728 East 136th Street, Suite 2A, Bronx, NY 10454, United States of America

Manufacturing: 7607 Boeing Drive, Greensboro, NC 27409 United States of America

Contacts: Phone - 718-402-2000, e-mail -sales@polytexink.com - www.POLYTEXUS.com