



Technical Data Sheet

Aquasafe House Wrap Printing Inks

Performance Features:

- Suitable for breathable house wrap printing
- Good printability and fast drying
- Excellent viscosity & pH stability
- Good water & cleaner resistance
- Adequate outdoor durability
- Low VOC & odor

Product Description:

The house wrap waterborne printing inks are designed for Gravure & Flexo printing with excellent adhesion on special House Wrap Laminate. .

Typical Properties:

Appearance:	Liquid
Solids:	32% - 38%
PH:	8.0 – 9.0
Viscosity, CPS:	250 - 500
Density:	1.1
Manufacturing location:	USA

Handling & Storage/Stability:

The product is stable under normal room temperature. Ideal storage temperature is 40°F to 80°F. This product should not be frozen or stored at the temperature that's above 100 °F for too long.

Market Uses:

- Non-woven house wrap printing
- Synthetic film house wrap printing

Application Methods:

- Gravure & Flexo printing

Color options:

- Pantone colors available upon request

Product Safety:

- SDS available upon request

POLYTEX® ENVIRONMENTAL INKS, INC.

We provide infinite solutions and first-class customer services
R&D: 728 East 136th Street, Suite 2A, Bronx, NY 10454, United States of America
Manufacturing: 7607 Boeing Drive, Greensboro, NC 27409 United States of America
Contacts: Phone - 718-402-2000, e-mail -sales@polytexink.com - www.POLYTEXUS.com