



## Technical Data Sheet Soft Touch Coating

### Product Description:

Aqueous soft touch coatings are designed for creating a luxurious feel to a variety of surfaces. Ideal for gravure or Flexo printing. The products have good adhesion and abrasion resistance on paper or films.

### Performance Features:

- Excellent Print quality
- Non-Burnishing
- Super low gloss
- High transparency
- Good water and alcohol resistance
- Very low VOC

### Typical Properties:

Appearance:	Off-white liquid
Solids:	24.5% - 28.5%
PH:	7.5 - 8.5
Viscosity, CPS:	300 - 600
Density:	1.0 - 1.05
Manufacturing location:	USA

### Handling & Storage/Stability:

The coatings are stable under normal room temperature. Ideal storage temperature is 40°F to 80°F. Prevent Freezing.

### Market Uses:

- Cosmetic/wine packaging
- Book cover
- Gift card
- Tag printing

### Application Methods:

- Gravure & Flexo printing
- Flexible solutions based on customers' applications
- 12-14 BCM coat weight is recommended

### Product Options:

- Customized formulations available for a range of haptic feel (silky- velvet)
- Formulations can be cross-linked for improved abrasion resistance

### Product Safety:

- SDS available upon request

## POLYTEX® ENVIRONMENTAL INKS, INC.

R&D: 728 East 136th Street, Suite 2A, Bronx, NY 10454, United States of America  
Manufacturing: 7607 Boeing Drive, Greensboro, NC 27409 United States of America  
Contacts: Phone - 718-402-2000, e-mail -sales@polytexink.com - www.POLYTEXUS.com